



# Grejni kablovi ELEKTRA VCDR

jednostro napajanje



tip	dužina [m]	snaga [W]
<b>20 W/m</b>		
VCDR 20/190	9,5	190
VCDR 20/235	12,0	235
VCDR 20/330	16,5	330
VCDR 20/380	19,0	380
VCDR 20/520	26,0	520
VCDR 20/600	29,0	600
VCDR 20/800	40,0	800
VCDR 20/1000	50,0	1000
VCDR 20/1140	57,0	1140
VCDR 20/1300	65,0	1300
VCDR 20/1560	78,0	1560
VCDR 20/1720	86,0	1720
VCDR 20/2050	102,0	2050
VCDR 20/2360	118,0	2360
VCDR 20/2710	135,0	2710
VCDR 20/3000	150,0	3000
VCDR 20/3450	175,0	3450

## > Tehnički podaci

Izlazna snaga	20 W/m <sup>2</sup>
Napajanje	230 V ~ 50/60Hz
Debljina kabla	~ 5 x 7 mm
Min. instalirana temperatura	-5°C
Max. radna temperatura	+ 95°C
Napojni kabl (hladan kraj)	1 x 4m, 3 x 1.0 mm <sup>2</sup> ili 3 x 1.5 mm <sup>2</sup>
Tip grejnog kabla:	dvožilni , jednostrano napajanje
Omotač grejnog kabla:	100% pokriven, PET pokriven aluminijumskom folijom, opleten tankim bakarnim omotačem
Izolacija	XLPE
Spoljni plašt kabla	otporan na toplotu i UV zračenja
Tolerancija otpornosti	-5%,-10%
Min. radijus savijanja kabla	3,5 D
Sertifikati proizvoda	UL, B, GOST-R
Sertifikati od ISO 9001	IQ NET, PCBC
Oznaka proizvoda	CE

